





LIQUID LEVEL INDICATION | GROUNDWATER | CONTAMINATED LAND

The Standard Dipmeter is a lightweight water level measuring instrument, designed for routine groundwater monitoring.



FEATURES

- Highly portable
- Delivery included
- 30m, 60m, and 100m lengths - longer available on request
- Lightweight
- Buzzer
- Light indicator
- 20,000 units sold worldwide
- Polyethylene tape
- EC Class II tape accuracy

BENEFITS

- Cost effective
- Reliable
- Field serviceable
- Use in a wide variety of applications
- Field proven
- Self test in field

APPLICATIONS

- Food Processing
- Groundwater levels
- Pump drawdown tests









TECHNICAL SPECIFICATIONS

PHYSICAL			
Power source	9V Battery		
Tape length	According to model selected: 30m, 60m, 100m		
Operating temperature	Reel: 100 °C Probe: 150 °C		
Reel seal	Silicone and epoxy resin		
DIMENSIONS AND WEIGHT			
Length	60m	60m	100m
Height	348mm	348mm	348mm
Width	270mm	270mm	270mm
Depth	200mm	200mm	200mm
Weight	4kg	6kg	7kg
Probe diameter	16mm		
Probe length	190mm		
MATERIALS OF MANUFACTURE			
Reel	Nylon disc, hub and electronic panel		
Main bearing	Delrin		
Frame	Polyurethane powder coated mild steel		
Fitting	Stainless steel (where possible)		
Probe	Stainless steel and Teflon®		
Electronic	Epoxy coated		
Tape	Linear medium density polyethylene, with two 7-strand stainless steel conductors with Kevlar reinforcement. Scale printed in black; unitary numbers in red Graduations: Metres, centimetres, millimetres Unitary metres in red, other markings in black		
Tape accuracy	EC Class II standard		



